




KET-MUM-100.4G



4G-LTE industrial modem with Ethernet output

- Industrial modem
- High reliability
- Compact size
- Main Safety Certifications

KET-MUM-100.4G is a device that integrates the latest generation of **4G-LTE modem**, a router and an **Ethernet output**.

The modem - router KET-MUM-100.4G guarantees **full freedom of installation** due to the external antenna with magnetic base with 3m cable and the hooks for wall mounting adapter.

KET-MUM-100.4G is compatible with all Italian mobile operators.

Technical Features	
General specifications	Protection range: ip30 Operative temperature: -20 ÷ +70 °c Storage temperature: -40 ÷ +85 °c Relative humidity: max 95% not condensing
Case	Dimensions: 100 x 23 x 100 mm (w x h x d) Mounting: wall/panel mounting with supplied supports Material: metal
Power supply	Supply voltage: 9 ÷ 26 vdc; 100 ÷ 240 vac with equipped power supply unit Consumption: standby: 80 ma ÷ 120 ma @ 12 v; operating: 200 ma ÷ 220 ma @ 12 v; peak: 240 ma @ 12 v Connectors types:
Ethernet interface	Supported protocols: lan/wan Communication rate: 1 x 10/100 mbps Connectors types: rj45
Modem	Supported protocols: 4g-lte Radio frequency: 850 ÷ 2100 mhz Antenna type: sma female Sim type: mini-sim
Integrated functions	Services: firewall, nat, dmz, vrrp
Certifications	Referends standard: en61000-4, iec60068-2-27, iec60068-2-32, iec60068-2-6 Approvals: ce (emc, lvd, rf, temperature), fcc, ccc, ptcrb, ic, rcm Security: data: ipsec/l2tp/pptp/gre/openssl/ca Metrology: