



Applications

Accounting

order code

KET-MPA-015



Flow meter for compressed air and gas insertion or inline

- Max pressure 16 bar
- Reliability of the measurement
- Can be installed in a pressurised system without interruption of flow
- Non-return protection

The KET-MPA flowmeter is based on the thermal mass flow rate and is ideal for measuring the flow of compressed air and gas.

Available as an insert for pipes from DN50 (2") to DN300 (12") or in-line for pipes from DN15 (1/2") to DN40 (1 1/2"). With the KET-MPA, the consumption of compressed air, nitrogen, CO2 or other non-corrosive and non-flammable gases can be measured up to a pressure of 16 bar (232 PSI). The insertion flow meter can be mounted/disassembled under pressure without interruption of the flow, safely with

non-return protection.

Technical Features	
General specifications	Protection Range: Inline: IP65 Operative Temperature: -20 ÷ +80 °C Storage Temperature: -20 ÷ +60 °C Relative Humidity: MAX 99% not condensing
General specifications	Protection Range: Inline: IP65 Operative Temperature: -20 ÷ +80 °C Storage Temperature: -20 ÷ +60 °C Relative Humidity: MAX 99% not condensing Supply Voltage: 18 ÷ 30 VAC / VDC Consumption: Max 200 mA Connectors types: Cable gland M16x1.5 (optional connector M12x1 8pol.)
General specifications	Protection Range: Inline: IP65 Operative Temperature: -20 ÷ +80 °C Storage Temperature: -20 ÷ +60 °C Relative Humidity: MAX 99% not condensing Supply Voltage: 18 ÷ 30 VAC / VDC Consumption: Max 200 mA Connectors types: Cable gland M16x1.5 (optional connector M12x1 8pol.)Supported Protocols: ModBUS RTU Communication Rate: Isolation: Connectors types:
General specifications	Protection Range: Inline: IP65 Operative Temperature: -20 ÷ +80 °C Storage Temperature: -20 ÷ +60 °C Relative Humidity: MAX 99% not condensing Supply Voltage: 18 ÷ 30 VAC / VDC Consumption: Max 200 mA Connectors types: Cable gland M16x1.5 (optional connector M12x1 8pol.)Supported Protocols: ModBUS RTU Communication Rate: Isolation: Connectors types: Channels: Analog Inputs: 4 - 20 mA for pressure sensor Precision: Resolution:
General specifications	Protection Range: Inline: IP65 Operative Temperature: -20 ÷ +80 °C Storage Temperature: -20 ÷ +60 °C Relative Humidity: MAX 99% not condensing Supply Voltage: 18 ÷ 30 VAC / VDC Consumption: Max 200 mA Connectors types: Cable gland M16x1.5 (optional connector M12x1 8pol.)Supported Protocols: ModBUS RTU Communication Rate: Isolation: Connectors types: Channels: Analog Inputs: 4 - 20 mA for pressure sensor Precision: Resolution: Channels: Pulse of lenght 0.02 ÷ 2 sec Voltage Output: