



Applications

Accounting

ModBUS thermal energy counter in accordance with EN1434

- 4 frequency inputs and 1 analogue input for flow meter
- Couple of PT500 temperature probes
- Large graphic display
- Available in MID version

KET-CCC-110 is a calculator with ModBUS RTU interface compatible with all types of flow meters: turbine, Woltmann, ultrasonic and electromagnetic.

The meter calculates heating and cooling consumption extremely accurately, also by means of an automatic switch. It is also useful for cogeneration or trigeneration plants.

It also acquires signals from cold/hot water sanitary meters or in any case traceable to impulsive and/or analogue

Inputs.

It has an F-RAM type data logger with permanent data storage capacity of up to one year.

Equipped with PT500 temperature probes selected in pairs, for the correct and necessary accuracy of the calculation.

The KET-CCC-110 is approved for "financial transactions" according to EN 1434 as per European Directive 2004/22EG, available in MID version (MI-004).

2004/22EG, available in MID version (MI-004).	
Technical Features	
General specifications	Protection Range: IP65 Operative Temperature: -5 ÷ +55 °C Storage Temperature: Relative Humidity:
General specifications	Protection Range: IP65 Operative Temperature: -5 ÷ +55 °C Storage Temperature: Relative Humidity: Dimensions: 125 x 179 x 68 mm (W x H x D) Mounting: DIN-rail Required DIN modules: 6 DIN modules Electric Board Type: Industrial Material: PC/ABS, Self extinguishing
General specifications	Protection Range: IP65 Operative Temperature: -5 ÷ +55 °C Storage Temperature: Relative Humidity: Dimensions: 125 x 179 x 68 mm (W x H x D) Mounting: DIN-rail Required DIN modules: 6 DIN modules Electric Board Type: Industrial Material: PC/ABS, Self extinguishing Supply Voltage: 100 ÷ 240 VAC (44-66 Hz) Consumption: 5 W Connectors types: Screw terminal
General specifications	Protection Range: IP65 Operative Temperature: -5 ÷ +55 °C Storage Temperature: Relative Humidity: Dimensions: 125 x 179 x 68 mm (W x H x D) Mounting: DIN-rail Required DIN modules: 6 DIN modules Electric Board Type: Industrial Material: PC/ABS, Self extinguishing Supply Voltage: 100 ÷ 240 VAC (44-66 Hz) Consumption: 5 W Connectors types: Screw terminal Memory Type: F-RAM: permanent storage of data in case of power failure Data Storage Capacity: 12 months
General specifications	Protection Range: IP65 Operative Temperature: -5 ÷ +55 °C Storage Temperature: Relative Humidity: Dimensions: 125 x 179 x 68 mm (W x H x D) Mounting: DIN-rail Required DIN modules: 6 DIN modules Electric Board Type: Industrial Material: PC/ABS, Self extinguishing Supply Voltage: 100 ÷ 240 VAC (44-66 Hz) Consumption: 5 W Connectors types: Screw terminal Memory Type: F-RAM: permanent storage of data in case of power failure Data Storage Capacity: 12 months Channels: Supported Protocols: ModBUS RTU Communication Rate: Isolation: Connectors types: Screw terminal