



KET-DIM-100

Applications

Building management system







Wireless control module with 0-10 V output

- Device control with 0-10 V input
- Designed for road applications
- Integrated repeater function
- Extended radio range

KET-DIM-100 is the **wireless** analog control module that enables effective remote control of a wide range of devices, including lamps, pumps, and motors, equipped with a standard **0-10 V** regulation input. Its **wireless** technology simplifies installation and offers greater flexibility in device control. Its **small dimensions** make it ideal for integration within lighting fixtures such as ceiling lights and street lamps, maintaining a compact and discreet design. The **protective resin coating**?ensures reliable operation even in the presence of vibrations and temperature fluctuations, guaranteeing greater durability over time. Thanks to the **integrated repeater function** and the **amplified radio**, the KET-DIM-100 allows for easy and cost-effective extension of the range and reliability of the **X-Monitor** network, fully leveraging the benefits of **IEEE 802.15.4 wireless communication**.

General specifications	Protection Range: IP65 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity:
General specifications	Protection Range: IP65 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity: Dimensions: 100 x 45 x 30 mm (W x H x D) Mounting: Wall mounting Material: Black nylon
General specifications	Protection Range: IP65 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity: Dimensions: 100 x 45 x 30 mm (W x H x D) Mounting: Wall mounting Material: Black nylon Supply Voltage: 230 VAC with integrated power supply (50-60 Hz) Consumption: 1.5 VA Connectors types: Device supplied with pre-skinned cable terminals
General specifications	Protection Range: IP65 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity: Dimensions: 100 x 45 x 30 mm (W x H x D) Mounting: Wall mounting Material: Black nylon Supply Voltage: 230 VAC with integrated power supply (50-60 Hz) Consumption: 1.5 VA Connectors types: Device supplied with pre-skinned cable terminals Channels: 1 Digital Inputs: For clean contact with control, alarm, pulse counter, second counter, etc. functions.
General specifications	Protection Range: IP65 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity: Dimensions: 100 x 45 x 30 mm (W x H x D) Mounting: Wall mounting Material: Black nylon Supply Voltage: 230 VAC with integrated power supply (50-60 Hz) Consumption: 1.5 VA Connectors types: Device supplied with pre-skinned cable terminals Channels: 1 Digital Inputs: For clean contact with control, alarm, pulse counter, seco counter, etc. functions. Output Type: Remote control of devices with a 10 V control input