kerberos



XCM-CTW-110

Applications

Stand alone

Versius

XCM-CTW-100

IP40

3xAA

Programmable battery-powered wireless Stand Alone thermostat

- **Weekly programming of eight different zones**
- **Large backlit LCD display**
- **Advanced pre-ignition and pre-shutdown functions**
- **3 batterie AA incluse**

The **XCM-CTW-110** is the Stand Alone chronothermostat of the MaggiorDOMO® system, perfect for controlling temperatures and programming in your house.Thanks to the visual menu and the large graphic display, **all information is easily accessible**. The backlight ensures excellent readability in all lighting conditions.The thermostat XCM-CTW-110 allows the weekly programming of up to **eight different zones** to ensure maximum comfort, with great attention to energy saving. The device also handles advanced features as pre-turning on and off.

Technical Features

General specifications	**Protection Range**: IP40 **Operative Temperature**: -5 ÷ +45 °C **Storage Temperature**: -20 ÷ +54 °C
Case	**Dimensions**: 125 x 97 x 23 mm (W x H x D) **Mounting**: Wall mounted or on standard box type 503
Battery power supply	**Supply Voltage**: 4.5 V **Battery Type**: 3 AA **Approximate Battery Life**: About 18 months
Radio module	**Supported Protocols**: IEEE 802.15.4 ZigBee Pro® **Radio Frequency**: 868 MHz ISM Band **Output Power**: -17 ÷ +4 dBm **Sensitivity**: -101 dBm **Antenna Type**: 1 internal **Max Distance (Free Air)**: Up to 150 m
Integrated functions	**Services**: Weekly programming of up to eight zones on three temperature levels, display alarm messages.
Temperature sensor	**Measure Range**: -10 ÷ +50 °C **Precision**: ± 0.5 °C
Certifications	**Referends Standard**: EN 60730-2-9, EN 301 489-3, EN 62311, EN 300 220-2 **Security**: Class III