



## KET-RMB-210.S

## **Applications**

Monitoring consumption

Building management system

**Smart City** 

Accounting









## Wireless amplified repeater for outdoor mounting

- Compact size
- Extended radio range
- Wide-ranging power supply flexibility
- Suitable for outdoor installation

The KET-RMB-210.S, together with the Gateway and the nodes with integrated Repeater functionality, provides the network infrastructure necessary for the correct transmission of data collected by wireless sensors. Its high degree of protection, IP65, makes it suitable for outdoor installation.

The ZigBee™ standard guarantees high reliability and resistance to interference, while the high sensitivity of the radio module can reach distances of over 1000 m in free air.

The standard antenna connector supports 90° joint antennas or wired ones for placement outside the electrical

Thanks to increased power, this device reduces the total number of nodes in the network.

Technical Features	
General specifications	Protection Range: IP65 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity:
General specifications	Protection Range: IP65 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity: Dimensions: 53,5 x 110 x 61 mm (W x H x D) Mounting: Wall mounting or on DIN rail with supplied supports Required DIN modules: 3 DIN modules Electric Board Type: Industrial or switchboard Material: Blend PC/ABS sel extinguishing UL94-VO
General specifications	Protection Range: IP65 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity: Dimensions: 53,5 x 110 x 61 mm (W x H x D) Mounting: Wall mounting or on DIN rail with supplied supports Required DIN modules: 3 DIN modules Electric Board Type: Industrial or switchboard Material: Blend PC/ABS sel extinguishing UL94-VO Supply Voltage: 12 ÷ 24 VDC, 12 ÷ 20 VAC; 230 VAC with integrated power supply Consumption: < 1.5 W @ 12 ÷ 20 VAC / < 1.5 W @ 12 ÷ 24 VDC / < 1.5 W @ 230 VAC Connectors types: Screw terminal
General specifications	Protection Range: IP65 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity: Dimensions: 53,5 x 110 x 61 mm (W x H x D) Mounting: Wall mounting or on DIN rail with supplied supports Required DIN modules: 3 DIN modules Electric Board Type: Industrial or switchboard Material: Blend PC/ABS sel extinguishing UL94-VO Supply Voltage: 12 ÷ 24 VDC, 12 ÷ 20 VAC; 230 VAC with integrated power supply Consumption: < 1.5 W @ 12 ÷ 20 VAC / < 1.5 W @ 12 ÷ 24 VDC / < 1.5 W @ 230 VAC Connectors types: Screw terminal Supported Protocols: X-Monitor Protocol (X-MP) / IEEE 802.15.4 / ZigBee™ Pro 2.0 Radio Frequency: 2.4 GHz ISM Band Output Power: +3 ÷ +20 dBm Sensitivity: -104 dBm Antenna Type: RPSMA connector, 90° antenna supplied Max Distance (Free Air): Over 1000 m
General specifications	Protection Range: IP65 Operative Temperature: -20 ÷ +60 °C Storage Temperature: Relative Humidity: Dimensions: 53,5 x 110 x 61 mm (W x H x D) Mounting: Wall mounting or on DIN rail with supplied supports Required DIN modules: 3 DIN modules Electric Board Type: Industrial or switchboard Material: Blend PC/ABS sel extinguishing UL94-VO Supply Voltage: 12 ÷ 24 VDC, 12 ÷ 20 VAC; 230 VAC with integrated power supply Consumption: < 1.5 W @ 12 ÷ 20 VAC / < 1.5 W @ 12 ÷ 24 VDC / < 1.5 W @ 230 VAC

Connectors types: Screw terminal Supported Protocols: X-Monitor Protocol (X-MP) / IEEE 802.15.4 / ZigBee™ Pro 2.0 Radio Frequency: 2.4 GHz ISM Band Output Power: +3 ÷ +20 dBm Sensitivity: -104 dBm Antenna Type: RPSMA connector, 90° antenna supplied Max Distance (Free Air): Over 1000 m Radio Signal Indicator: Integrated (LinkQuality)
Output Power Adjustment: From local keyboard and remotely

Output Power Adjustment: From local keyboard and remotely

Firmware Upgrade: Via radio