

XCM-CTW-100.R



APPLICATIONS
For residential
For the community



MAGGIORI CONTENUTI ONLINE

Wireless programmable battery powered thermostat with relay contact

- Relay for automatic on/off of a zone valve
- Weekly programming of eight different zones
- Large backlit LCD display
- Indication of outdoor temperature and humidity

The **XCM-CTW-100.R** is the chronothermostat with relay of the MaggiorDOMO® system, perfect for controlling temperatures and programming in your flat.

The **relay** output allows automatic control of the switching on/off of a zone valve, that is the valve normally present on the manifold of ring systems. Through the visual menu and the large graphic display the user can access the total consumption, for each zone and for single heating body of the accommodation. The power and configuration data of each heating body are also visible. The backlight ensures excellent readability in all lighting conditions. The thermostat XCM-CTW-100.R allows the weekly programming of up to **eight different zones** to ensure maximum comfort, with great attention to energy saving. The device also handles advanced features as pre-turning on and off. With a simple touch, you can view the outdoor temperature and humidity, to always know the weather! The connection to the building network enables **remote diagnosis** of any problem, keeping the user from problems and reducing maintenance costs.

Possibility of use with MaggiorDOMO® APP from smartphone or tablet (IOS, Android).

TECHNICAL FEATURES	
GENERAL SPECIFICATIONS	Protection Range: IP40 Operative Temperature: -5 ÷ +45 °C Storage Temperature: -20 ÷ +54 °C Relative Humidity:
CASE	Dimensions: 125 x 97 x 23 mm (W x H x D) Mounting: Wall mounted or on standard box type 503 Material:
BATTERY POWER SUPPLY	Supply Voltage: 4.5 V Battery Type: 3 AA Approximate Battery Life: About 18 months Consumption:
RELE' OUTPUTS	Channels: Unipolar Contact Relays Voltage Output: 250 VAC Maximum Rated Current: 5 A Isolation:
RADIO MODULE	Supported Protocols: IEEE 802.15.4 ZigBee Pro® Radio Frequency: 868 MHz ISM Band Output Power: -17 ÷ +4 dBm Sensitivity: -101 dBm Antenna Type: 1 internal Max Distance (Free Air): Up to 150 m
INTEGRATED FUNCTIONS	Services: Weekly programming of up to eight zones on three temperature levels, user counters visualization, connection to the system's wireless backbone, no need for a Wi-Fi network. External temperature and humidity display, display alarm messages.
TEMPERATURE SENSOR	Measure Range: -10 ÷ +50 °C Precision: ± 0.5 °C Repeatability: Resolution:
CERTIFICATIONS	Referends Standard: EN 60730-2-9, EN 301 489-3, EN 62311, EN 300 220-2 Approvals: Security: Class II Metrology:



No Information