## XCM-ATW-110





## Electronic actuator Stand Alone for radiators and fan coils

- Wireless communication with chronothermostat
- Adjustment +/- 3°C and local OFF control
- Automatic anti-block function
- Battery life over 3 seasons

The electronic actuator **XCM-ATW-110**, for MaggiorDOMO® Stand Alone system, regulates indoor comfort based on the commands from the chronothermostat. The **small size** allows for installation directly on the collector. The easy local control and the clear indication by LED allow to **customize the temperature** controlling of each actuator. The advanced radio technology and patented movement system guarantee battery life of more than 3 seasons or 45000 movements.

| TECHNICAL FEATURES     |   |
|------------------------|---|
| GENERAL SPECIFICATIONS | Protection Range: IP30<br>Operative Temperature: 0 ÷ +85 °C<br>Storage Temperature: -15 ÷ +60 °C<br>Relative Humidity: MAX 80% not condensing   |
| CASE                   | Dimensions: 47 x 91 x 62 mm (W x H x D)<br>Flanged Connections: M30 x 1.5 mm<br>Compatible Valves: IVAR, Caleffi, FAR (with appropriate adapter), Giacomini (with appropriate<br>adapter), IVR, Oventrop, RBM, Pocetti (with appropriate adapter), ICMA (with appropriate adapter).<br>For more compatibility contact the manufacturer.<br>Insulation Class: Class III<br>Material: |
| BATTERY POWER SUPPLY   | Supply Voltage: 4.5 V<br>Battery Type: 3 AA<br>Approximate Battery Life: > 3 seasons<br>Consumption:  |
| RADIO MODULE           | Supported Protocols: IEEE 802.15.4 ZigBee Pro®<br>Radio Frequency: ISM Band 868 MHz<br>Output Power: -17 ÷ +4 dBm<br>Sensitivity: -101 dBm<br>Antenna Type: 1 internal<br>Max Distance (Free Air): Up to 150 m  |
| FUNCTIONALITY          | Radio Signal Indicator: LED displays<br>Output Power Adjustment:<br>Firmware Upgrade:   |
| INTEGRATED FUNCTIONS   | Services: Modulating regulation, wieless communication with programmable thermostat.<br>Automatic anti-block function, adjustment +/- 3 ° C and OFF command locally, self-adaptation<br>function according to the valve, Advanced Battery Management  |
| CERTIFICATIONS         | Referends Standard: EN 60950-1, EN 301 489-3, EN 62311, EN 300 220-2<br>Approvals:<br>Security:<br>Metrology:   |

|             | APPLICATIONS |
|-------------|--------------|
| Stand Alone |              |
|             |              |



MAGGIORI CONTENUTI ONLINE

