




## **KET-MUM-100.4G**



## 4G-LTE industrial modem with Ethernet output

- Industrial modem
- High reliability
- Compact size
- Main Safety Certifications

**KET-MUM-100.4G** is a device that integrates the latest generation of **4G-LTE modem**, a router and an **Ethernet output.** 

The modem - router KET-MUM-100.4G guarantees **full freedom of installation** due to the external antenna with magnetic base with 3m cable and the hooks for wall mounting adapter. KET-MUM-100.4G is compatible with all Italian mobile operators.

Technical Features	
General specifications	Protection Range: IP30 Operative Temperature: -20 ÷ +70 °C Storage Temperature: -40 ÷ +85 °C Relative Humidity: MAX 95% not condensing
Case	Dimensions: 100 x 23 x 100 mm (W x H x D)  Mounting: Wall/Panel mounting with supplied supports  Material: Metal
Power supply	Supply Voltage: 9 ÷ 26 VDC; 100 ÷ 240 VAC with equipped power supply unit Consumption: Standby: 80 mA ÷ 120 mA @ 12 V; Operating: 200 mA ÷ 220 mA @ 12 V; Peak: 240 mA @ 12 V Connectors types:
Ethernet interface	Supported Protocols: LAN/WAN Communication Rate: 1 x 10/100 Mbps Connectors types: RJ45
Modem	Supported Protocols: 4G-LTE Radio Frequency: 850 ÷ 2100 MHz Antenna Type: SMA female SIM Type: Mini-SIM
Integrated functions	Services: Firewall, NAT, DMZ, VRRP
Certifications	Referends Standard: EN61000-4, IEC60068-2-27, IEC60068-2-32, IEC60068-2-6 Approvals: CE (EMC, LVD, RF, Temperature), FCC, CCC, PTCRB, IC, RCM Security: Data: IPsec/L2TP/PPTP/GRE/OpenVPN/CA Metrology: