



KET-AIR-210

Applications

Versus

KET-AIR-200

KET-TLP-110

ModBUS sensor for indirect CO2 and air quality measurement

- Innovative e-ink display always visible
- Perfect integration into BMS / BEMS systems
- Integrated thermostat function
- Internal memory

Considering that people spend up to **90% of their time indoors**, the presence of **gaseous pollutants**, particularly **Volatile Organic Compounds (VOCs)**, is significantly higher compared to open spaces. In high-density environments such as offices, schools, hospitals, and other **public premises**, especially in modern buildings characterized by **poor air exchange**, there is an increase in the concentration of **carbon dioxide (CO2)** produced by human activity. These negative indoor environmental conditions can significantly impact **people's well-being**, contributing to health problems, **decreased concentration**, and reduced **productivity**. The **KET-AIR-210** device uses an indirect method of measuring **CO2** based on a **MOX technology sensor**, which estimates the amount of carbon dioxide by detecting the hydrogen concentration. Combined with a sensor dedicated to measuring **Volatile Organic Compounds (VOCs)**, the KET-AIR-210 allows for the implementation of effective measures to increase and improve **ventilation efficiency** and **air purification**, creating healthier and more comfortable indoor environments. The **KET-AIR-210** also integrates high-precision sensors for measuring **Temperature**, **Relative Humidity**, and **Ambient Light**, and is equipped with an **RS485 ModBUS RTU Slave** interface, facilitating integration with control and data acquisition systems. The **KET-AIR-210.DY version** is equipped with a **zero-power e-ink display** that provides users with detailed information on the level of **thermal comfort** present in the environment, ensuring **optimal and continuous reading** of the detected parameters with **minimal energy consumption**. The **KET-AIR-210.TS version** allows the user to **set the desired comfort**

Technical Features	
General specifications	Protection Range: IP40 Operative Temperature: -10 ÷ +60 °C Storage Temperature: -15 ÷ +60 °C Relative Humidity: MAX 80% not condensing
Case	Dimensions: 100 x 100 x 22.5 mm (W x H x D) Mounting: Panel mounting with supplied supports Material: ABS, self extinguishing: UL 94 V-0
Power supply	Supply Voltage: 5 ÷ 12 VDC Connectors types: Removable spring clamps
Datalogger function	Memory Type: Internal Flash (only for .DL version) Data Storage Capacity: Retention of more than 60,000 data with date and hour even if there is no connection
Rs485 interface	Supported Protocols: ModBUS RTU Slave Communication Rate: 9.6, 19.2, 38.4 o 57.6 Kpbs Connectors types: Removable spring clamps
Functionality	User menu: Thermostat function with temperature summer / winter mode, comfort / saving / off mode, air speed setting, (only .TS version) Support for public environment: Anti-removal support, keyboard lock and active function limitation
Temperature sensor	Sensor Type: Digital Measure Range: -40 ÷ +123.8 °C Precision: ±0.4 ÷ 25 °C Repeatability: ±0.1 °C Resolution: ±0.01 °C
Humidity sensor	Measure Range: 0 ÷ 100%RH Precision: ±3%RH from 20 to 80%RH Repeatability: ±0.1%RH Resolution: ±0.03%RH Hysteresis: ±1%RH Long Period Stability: <0.5%RH/year

Technical Features

Light sensor	Number of sensors: 2, on front and on top Measure Range: 10 ÷ 1000 Lux Response Curve: Similar to that of the human eye
Volatile organics compounds sensor	Measure Range: 0 ÷ 60000 ppb Accuracy: ±15% ppb Resolution: ±0.2% ppb
Co2 sensor	Principle of Operation: Indirect Measure Range: 400 ÷ 60000 ppm Accuracy: ±10% ppm Resolution: ±0.2% ppm