



Articolo Senza Titolo



| TECHNICAL FEATURES     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GENERAL SPECIFICATIONS | <b>Protection Range:</b> IP67<br><b>Operative Temperature:</b> -25 ÷ +65 °C<br><b>Storage Temperature:</b><br><b>Relative Humidity:</b>                                                                                                                                                                                                                                                                                                                                                            |
| GAS FLOW METER         | <b>Principle of Operation:</b> Gas velocity measurement<br><b>Max Project Pressure:</b> 20 bar<br><b>Precision:</b> $Q_{min} = Q < Q_t \pm 3\%$ & $Q_t = Q = Q_{max} \pm 1,5\%$<br><b>Material:</b><br><b>Flanged Connections:</b> PN 16 o ANSI 150<br><b>Calibre:</b> G 40 ÷ 650<br><b>Tube Diameter:</b> Ø 50 ÷ 100 mm<br><b>Standard Flow Direction:</b> Horizontal (high - low on request)<br><b>Lubrication Pump:</b> Yes<br><b>Top:</b> With mechanical totaliser with dual pulse emitter BF |
| CERTIFICATIONS         | <b>Referends Standard:</b> OIML R6, OIML R32, EN12261, EEC<br><b>Approvals:</b><br><b>Security:</b><br><b>Metrology:</b>                                                                                                                                                                                                                                                                                                                                                                           |



MAGGIORI CONTENUTI ONLINE

