



APPLICATIONS
Building management system



MAGGIORI CONTENUTI ONLINE

# OMNI directional antenna with high gain 5 dBi, multiband GSM/LTE and 5 mt cable

- Wide frequency band (698~960/1710~2700)
- Ideal for GSM/LTE/CDMA/PCS/W-LAN systems
- High gain 5 dBi
- 5 mt cable with SMA-m connector

The **KET-AGA-005.05** is a high gain (**5 dBi**) Multi-band Omnidirectional Antenna with a wide frequency band (698~960/1710~2700), low standing wave, strong anti-interference capability, ideal for 3G (GSM), 4G (LTE), CDMA, PCS and W-LAN systems.  
Thanks to its high degree of protection, IP65, can be installed in both industrial and outdoor environments. It is equipped with a 5 m cable with SMA-m connector.

TECHNICAL FEATURES	
ANTENNA SPECIFICATIONS	<b>Protection Range:</b> IP65 <b>Operative Temperature:</b> -40 ÷ +60 °C <b>Dimensions:</b> Ø 60 mm; W 230 mm <b>Connections:</b> 5 m cable <b>Connectors types:</b> SMA male <b>Radio Frequency:</b> 698~960/1710~2700 MHz <b>Gain:</b> 5 dBi

