



Wireless infrared remote control for controlling air conditioners and heat pumps

- Large library of supported devices
- IR receiver for acquisition of custom commands
- Supports multiple devices simultaneously
- Perfect integration into BMS / BEMS systems

KET-WIR-100 is an **infrared remote control** capable of controlling a wide range of air conditioners and heat pump systems. Using KET-WIR-100 it becomes simple to integrate cooling or heating elements in building energy management systems (BMS / BEMS).
Management can be direct or intermediated by the supervision system.
Suitable for use in public environments supports keyboard lock and limitation of active functions.

APPLICATIONS
Air Quality
Building management system



MAGGIORI CONTENUTI ONLINE

TECHNICAL FEATURES	
GENERAL SPECIFICATIONS	Protection Range: IP40 Operative Temperature: -10 ÷ +60 °C Storage Temperature: -20 ÷ +70 °C Relative Humidity: MAX 85% not condensing
CASE	Dimensions: 100 x 100 x 22.5 mm (W x H x D) Mounting: Panel mounting with supplied supports Material: ABS, self extinguishing: UL 94 V-O
POWER SUPPLY	Supply Voltage: 5 ÷ 12 VDC Consumption: Connectors types: Removable spring clamps
IR INTERFACE	Max distance: 3 m Learning mode: Supported Supported devices: Available on web site (use QR Code for quick access)
DIGITAL INPUTS	Channels: 1 for drycontact Digital Inputs:
RADIO MODULE	Supported Protocols: X-Monitor Protocol (X-MP) / IEEE 802.15.4 Radio Frequency: 2.4 GHz Output Power: +20 dBm Sensitivity: -101 dBm Antenna Type: Internal Max Distance (Free Air): Over 600 m
FUNCTIONALITY	Radio Signal Indicator: Integrated (LinkQuality) Output Power Adjustment: From local menu and remotely Firmware Upgrade: Over The Air and via USB C connector User menu: Thermostat function with temperature summer / winter mode, comfort / saving / off mode, air speed setting, (only .TS version) Support for public environment: Anti-removal support, keyboard lock and active function limitation
TEMPERATURE SENSOR	Sensor Type: NTC or digital (Only .TH version) Measure Range: -40 ÷ +123.8 °C Precision: ±0.4 ÷ 25 °C Repeatability: ±0.1 °C Resolution: ±0.01 °C
HUMIDITY SENSOR	Version: Only .TH version Measure Range: 0 ÷ 100%RH Precision: ±3%RH from 20 to 80%RH Repeatability: ±0.03%RH Resolution: ±1%RH Hysteresis: ±1%RH Long Period Stability: <0.5%RH/year



No Information