



Wireless 4-buttons command

- 4 buttons with simple or complex controls
- LED alert command
- Extended radio range
- Suitable for industrial environments

The **KET-PSC-400** has four buttons that can be used as a control element in **industrial environments**. Using with the controllers of the X-Monitor it can execute simple or complex commands (timed pressure, double-click, etc.) for the activation of different features.
The indicator LEDs incorporated can be controlled remotely indicating the success of the operation.
The C-cell batteries provide a **high level of autonomy** while the degree of protection makes it suitable for even the harshest environments.
The command KET-PSC-400 uses the network X-Monitor already.
It comes with membranes of different type to adapt to the most varied requirements.

TECHNICAL FEATURES	
GENERAL SPECIFICATIONS	Protection Range: IP65 Operative Temperature: -10 ÷ +70 °C Storage Temperature: -20 ÷ +85 °C Relative Humidity: MAX 80% not condensing
CASE	Dimensions: 80 x 81 x 56 mm (W x H x D) Mounting: Wall mounting Material: PC/ABS, Self extinguishing: UL 94 V-O
BATTERY POWER SUPPLY	Supply Voltage: 2 x 1.5 V Battery Type: 2 type C, half torch Approximate Battery Life: > 3 years Consumption:
RADIO MODULE	Supported Protocols: X-Monitor Protocol (X-MP) / IEEE 802.15.4 / ZigBee™ Pro 2.0 Radio Frequency: 2.4 GHz ISM Band Output Power: +3 ÷ +20 dBm Sensitivity: -101 dBm Antenna Type: 1 internal Max Distance (Free Air): Over 600 m
FUNCTIONALITY	Radio Signal Indicator: Integrated (LinkQuality) Output Power Adjustment: From remotely Firmware Upgrade: Via radio
INTEGRATED FUNCTIONS	Services: Function management via wireless commands. Maintaining the state of association to the network after a power failure.

APPLICATIONS
Building management system
Thermoregulation



MAGGIORI CONTENUTI ONLINE

