




KET-MUM-100.4G



4G-LTE industrial modem with Ethernet output

- Industrial modem
- High reliability
- Compact size
- Main Safety Certifications

KET-MUM-100.4G is a device that integrates the latest generation of **4G-LTE modem**, a router and an **Ethernet output.**

The modem - router KET-MUM-100.4G guarantees **full freedom of installation** due to the external antenna with magnetic base with 3m cable and the hooks for wall mounting adapter. KET-MUM-100.4G is compatible with all Italian mobile operators.

Technical Features	
General specifications	Protection Range: IP30 Operative Temperature: -20 ÷ +70 °C Storage Temperature: -40 ÷ +85 °C Relative Humidity: MAX 95% not condensing
General specifications	Protection Range: IP30 Operative Temperature: -20 ÷ +70 °C Storage Temperature: -40 ÷ +85 °C Relative Humidity: MAX 95% not condensing Dimensions: 100 x 23 x 100 mm (W x H x D) Mounting: Wall/Panel mounting with supplied supports Material: Metal
General specifications	Protection Range: IP30 Operative Temperature: -20 ÷ +70 °C Storage Temperature: -40 ÷ +85 °C Relative Humidity: MAX 95% not condensing Dimensions: 100 x 23 x 100 mm (W x H x D) Mounting: Wall/Panel mounting with supplied supports Material: Metal Supply Voltage: 9 ÷ 26 VDC; 100 ÷ 240 VAC with equipped power supply unit Consumption: Standby: 80 mA ÷ 120 mA @ 12 V; Operating: 200 mA ÷ 220 mA @ 12 V; Peak: 240 mA @ 12 V Connectors types:
General specifications	Protection Range: IP30 Operative Temperature: -20 ÷ +70 °C Storage Temperature: -40 ÷ +85 °C Relative Humidity: MAX 95% not condensing Dimensions: 100 x 23 x 100 mm (W x H x D) Mounting: Wall/Panel mounting with supplied supports Material: Metal Supply Voltage: 9 ÷ 26 VDC; 100 ÷ 240 VAC with equipped power supply unit Consumption: Standby: 80 mA ÷ 120 mA @ 12 V; Operating: 200 mA ÷ 220 mA @ 12 V; Peak: 240 mA @ 12 V Connectors types: Supported Protocols: LAN/WAN Communication Rate: 1 x 10/100 Mbps Connectors types: RJ45
General specifications	Protection Range: IP30 Operative Temperature: -20 ÷ +70 °C Storage Temperature: -40 ÷ +85 °C Relative Humidity: MAX 95% not condensing Dimensions: 100 x 23 x 100 mm (W x H x D) Mounting: Wall/Panel mounting with supplied supports Material: Metal Supply Voltage: 9 ÷ 26 VDC; 100 ÷ 240 VAC with equipped power supply unit Consumption: Standby: 80 mA ÷ 120 mA @ 12 V; Operating: 200 mA ÷ 220 mA @ 12 V; Peak: 240 mA @ 12 V Connectors types: Supported Protocols: LAN/WAN Communication Rate: 1 x 10/100 Mbps Connectors types: RJ45 Supported Protocols: 4G-LTE Radio Frequency: 850 ÷ 2100 MHz Antenna Type: SMA female SIM Type: Mini-SIM
General specifications	Protection Range: IP30 Operative Temperature: -20 ÷ +70 °C Storage Temperature: -40 ÷ +85 °C Relative Humidity: MAX 95% not condensing Dimensions: 100 x 23 x 100 mm (W x H x D) Mounting: Wall/Panel mounting with supplied supports Material: Metal Supply Voltage: 9 ÷ 26 VDC; 100 ÷ 240 VAC with equipped power supply unit Consumption: Standby: 80 mA ÷ 120 mA @ 12 V; Operating: 200 mA ÷ 220 mA @ 12 V; Peak: 240 mA @ 12 V Connectors types: Supported Protocols: LAN/WAN Communication Rate: 1 x 10/100 Mbps Connectors types: RJ45 Supported Protocols: 4G-LTE Radio Frequency: 850 ÷ 2100 MHz Antenna Type: SMA female SIM Type: Mini-SIM Services: Firewall, NAT, DMZ, VRRP