



## KET-PMT-247

**Applications** 

Monitoring consumption



## Panel-mounted, three-phase power meter for current transformers

- Visualization of active and reactive energy
- RS485 ModBUS-RTU protocol
- 4DI+2DI+Pulse output
- Panel-mounting 96x96 mm

**KET-PMT-247** is a panel-mounted energy meter for **measuring energy** and main **electrical parameters** in industrial and civil environments, with built-in RS485 ModBUS RTU communication.

It has 4 dry contact digital inputs, 2 relay outputs and 1 pulse output.

Interface with high-brightness LED/LCD display, parameter setting and push-button control, ideal for real-time energy monitoring systems. It can directly replace traditional power transmitters and measuring instruments.

The KET-PMT-247 can be used in all kinds of control systems, SCADA systems and energy management systems.

Technical Features	
General specifications	Protection Range: IP20 Operative Temperature: -25 ÷ +65 °C Storage Temperature: -40 ÷ +80 °C Relative Humidity: MAX 93% not condensing
General specifications	Protection Range: IP20 Operative Temperature: -25 ÷ +65 °C Storage Temperature: -40 ÷ +80 °C Relative Humidity: MAX 93% not condensing Dimensions: 90 x 90 x 77.4 mm (W x H x D); faceplate 96 x 96 mm; cutout 92 x 92 mm Mounting: Panel Required DIN modules: Electric Board Type: Industrial or switchboard Material:
General specifications	Protection Range: IP20 Operative Temperature: -25 ÷ +65 °C Storage Temperature: -40 ÷ +80 °C Relative Humidity: MAX 93% not condensing Dimensions: 90 x 90 x 77.4 mm (W x H x D); faceplate 96 x 96 mm; cutout 92 x 92 mm Mounting: Panel Required DIN modules: Electric Board Type: Industrial or switchboard Material: Supply Voltage: 85 ÷ 265 VAC or 24 VDC (±20%) or 48 VDC (±20%) Consumption: =<10 VA Connectors types: Removable screw terminals
General specifications	Protection Range: IP20 Operative Temperature: -25 ÷ +65 °C Storage Temperature: -40 ÷ +80 °C Relative Humidity: MAX 93% not condensing Dimensions: 90 x 90 x 77.4 mm (W x H x D); faceplate 96 x 96 mm; cutout 92 x 92 mm Mounting: Panel Required DIN modules: Electric Board Type: Industrial or switchboard Material: Supply Voltage: 85 ÷ 265 VAC or 24 VDC (±20%) or 48 VDC (±20%) Consumption: =<10 VA Connectors types: Removable screw terminals Insertion Types: Three phase, three or four wires Connection: CT Current Inputs: 5 A @ 45 ÷ 65 Hz Voltage Inputs: 3x57.7/100 VAC (100 V), 3x220/380 VAC (400 V), 3x380/660 VAC (660 V) Start-up Current: Maximum Rated Current: Overload: 1.2 times the rated current (continuous); 10 times the rated current lasting for 1 second Minimum Current: Accuracy: Frequency: 0.05Hz   Current, Voltage: 0.2 class   Reactive power: 1.0 class   Reactive Electric energy: 1.0 class   Active power: 0.5 class   Active electric energy: 0.5 class Connections: Removable screw terminals ESD Protection: Between Power supply / Switching Output / Current Input / Voltage Input and Transmitting / Communication / Pulse Output / switching input AC 2 kV 1min; Between Transmitting, Communication, Pulse Output, Suntching input AC 1kV 1 min.

Configuration: By keyboard